

# Technical data sheet for NEW ACCZENT TERRA

High-quality heterogeneous compact vinyl floorcovering, glass fibre stabilized. Clear 0.8 mm wearlayer, class T.

PUR reinforcement for easy maintenance.

| Technical data                           | Standards                  | NEW ACCZENT TERRA                                    |
|------------------------------------------|----------------------------|------------------------------------------------------|
| Type of floor covering                   | EN 649                     | Compact heterogeneous vinyl floorcovering            |
| Classification                           | EN 685                     | Commerciali: 34<br>Industrial: 43                    |
| Wear layer thickness                     | EN 429                     | 0.8 mm                                               |
| PUR<br>(polyurethane surface protection) |                            | Yes                                                  |
| Total thickness                          | EN 428                     | 2.0 mm                                               |
| Total weight/m <sup>2</sup>              | EN 430                     | 2.800 gr/m <sup>2</sup>                              |
| Dimensional stability                    | EN 434                     | ≤ 0,10 %                                             |
| Abrasion Thickness loss                  | EN 660: Part I             | Group T: < 0.08 mm                                   |
| Residual indentation                     | EN 433                     | approx. 0.05 mm                                      |
| Castors chair test                       | EN 425                     | suitable                                             |
| Static electrical charge                 | EN 1815                    | < 2 kV                                               |
| Electrical properties                    | EN 1081                    | R <sub>1</sub> > 10 <sup>10</sup> Ohms               |
| Underfloor heating                       |                            | suitable – max. 27°C                                 |
| Impact sound reduction                   | EN ISO 140-8               | 5 dB                                                 |
| Thermal resistance                       |                            | suitable                                             |
| Reaction on fire                         | EN 13501-1                 | Class Cfl s1                                         |
| Light fastness                           | EN ISO 105-B02             | ≥ level 6                                            |
| Chemical resistance                      | EN 423                     | good resistance                                      |
| Fungi and Bacteria resistance            | DIN EN 846-A/C             | Sanitized <sup>®</sup> - Grade 0 - high fungi effect |
| Slip resistance                          | DIN 51130                  | R10                                                  |
| Colours                                  |                            | 12                                                   |
| Form of delievery                        | EN 426<br>Sheet<br>(rolls) | 23 running metres x 200 cm                           |

| Color No. | Welding rod No. |
|-----------|-----------------|
|-----------|-----------------|

|           |            |
|-----------|------------|
| CH 235 21 | 3291 839 6 |
| CH 235 22 | 3288 388 6 |
| CH 235 25 | 3291 929 6 |
| CH 235 27 | 3294 727 6 |
| CH 235 32 | 1292 322   |
| CH 235 37 | 3288 385 6 |
| CH 235 55 | 3288 387 6 |
| CH 235 57 | 3291 808 6 |
| CH 235 75 | 3288 386 6 |
| CH 235 77 | 3288 384 6 |
| CH 235 85 | 3292 453 6 |
| CH 235 87 | 3288 389 6 |